


MOULDED ELBOW (BUTWELD TYPE)



AVAILABLE M.O.C. :

PP (POLYPROPYLENE)
HDPE (HIGH DENSITY POLYETHYLENE)
ISOTACTIC PP
PVDF (POLYVINYLIDENE FLUORIDE)


ALL DIMENSIONS ARE IN MM (±2 MM)

SIZE IN.	MM	C	Ø D	Ø D1	Ø D2	L ±1
½ "	20	35.5	14.0	21.0	23.0	3.0
¾ "	25	40.0	19.0	25.0	28.0	4.0
1 "	32	48.0	24.0	32.0	35.5	5.0
1 ¼ "	40	60.0	29.0	40.0	43.0	6.0
1 ½ "	50	71.0	37.0	50.0	54.0	8.0
2 "	63	80.0	47.5	63.0	65.0	10.0
2 ½ "	75	90.0	59.0	75.0	78.0	12.0
3 "	90	109.0	73.0	90.0	95.0	14.0
4 "	110	135.0	88.0	108.5	114.0	15.0
5 "	125	159.0	125.0	125.0	103.0	---
5 ½ "	140	168.0	140.0	140.0	112.0	---
6 "	160	220.0	133.5	158.5	169.0	16.0
7 "	180	225.0	180.0	150.0	190.0	7.0
8 "	200	247.0	200.0	174.0	203.0	15.0

AS PER IS :8008 - 1976 (PART I)
MAX. WORKING PRESSURE 10kg / cm²

MOULDED ELBOW (SOCKET TYPE Plain)

(Only in P.P.)



ALL DIMENSIONS ARE IN MM (±2 MM)

SIZE IN.	MM	C	Ø D	Ø D1	L
½ "	20	28	21	26	16
¾ "	25	33	25	31	19
1 "	32	39	32	41	20
1 ¼ "	40	48	41	48	22
1 ½ "	50	58	50	60	29
2 "	63	67	64	74	29
2 ½ "	75	79	76	88	37
3 "	90	96	91	105	42
4 "	110	111	110	127	46
6 "	160	170	161	180	85

AS PER IS :8008 - 1976 (PART III)
MAX. WORKING PRESSURE 10kg / cm²



MOULDED ELBOW (THREADED TYPE)

(Only in P.P.)

AVAILABLE SIZE : ½", ¾", 1"